

CUMMINGS & LOCKWOOD

A Partnership of
Professional Corporations

Four Stamford Plaza
P.O. Box 120
Stamford, CT 06904-0120
203-327-1700
Fax 203-351-4535
www.cl-law.com

Greenwich
Hartford
New Haven
Bonita Springs
Naples
Palm Beach

jc551 U.S. PTO
09/250340
02/16/99

jc558 U.S. PTO
02/16/99

February 16, 1999

Scott D. Wofsy
203-351-4289
swofsy@cl-law.com

Case Docket No.: **TAY-101**

BOX PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent Application of:

Inventor(s): **Sia Yik HEI**

For: **IMPROVEMENTS IN CODE BASED ACCESS SYSTEMS**

Enclosed are:

X	23 page Application, including 5 pages of claims and 1 page of Abstract
X	5 sheets of Informal Drawings
X	Express Mail Certificate No. EM233518589US
	An assignment of the invention with recordation cover sheet
	A check in the amount of \$40.00 for recording the assignment
	Three Verified Statements Claiming Small Entity Status (Independent Inventor and Small Business Concerns)
X	Preliminary Amendment
X	Declaration, Power of Attorney and Petition (unexecuted)
	A Certified Copy of priority document
	A check in the amount of _____ to cover the application filing fee, as determined below
X	Before calculating the fee, cancel Claims <u>33-34</u>
	Associate Power of Attorney

09250340-021699

February 16, 1999


The filing fee has been calculated as shown below:

	(Col. 1)	(Col. 2)	SMALL	ENTITY	OR	OTHER THAN A SMALL	ENTITY
FOR:	NO. FILED	NO. EXTRA	RATE	FEE		RATE	FEE
BASIC FEE				\$380	OR		\$760.00
TOTAL CLAIMS	[32]-20 =	*[12]	X 11 =	0	OR	X 18 =	\$216.00
INDEP. CLAIMS	[2]- 3 =	*[3]	X 40 =	0	OR	X 80 =	\$0
	MULTIPLE DEPENDENT CLAIM PRESENTED		+125 =	\$	OR	+250 =	\$0
			TOTAL	0	OR	TOTAL	\$976.00

*If the difference in Col. 1 is less than zero, enter "0" in Col. 2

AUTHORIZATION TO CHARGE DEPOSIT ACCOUNT

X	The Commissioner is hereby authorized to charge the required fee of \$976.00 to Deposit Account No. 11-0231. A DUPLICATE COPY OF THIS SHEET IS ENCLOSED.
	The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Account No. 11-0231. A DUPLICATE COPY OF THIS SHEET IS ENCLOSED.

Respectfully submitted,
CUMMINGS & LOCKWOOD

 Scott D. Wofsy
 Reg. No.: 35,413

Dated: February 16, 1999

Mailing Address:

CUMMINGS & LOCKWOOD
 Scott D. Wofsy
 Cummings & Lockwood
 Granite Square
 700 State Street, P.O. Box 1960
 Stamford, CT 06904-0120
 (203) 351-4289

09540 04605260

(TAY-101)

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)
Sia Yik HEI) Examiner: Unassigned
Serial No.: Unassigned) Group Art Unit: Unassigned
Filed: February 16, 1999)
For: IMPROVEMENTS IN CODE)
BASED ACCESS SYSTEMS)

BOX PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Dear Sir:

Prior to examination of the subject application and calculation of the filing fees therefor, please amend the claims as follows:

IN THE CLAIMS:

Please amend Claims 3-9, 13-16, 19-25 and 29-32 as follows:

Claim 3, line 1, delete "or 2" after the numeral 1;

Claim 4, line 1, delete "or 2" after the numeral 1;

Claim 5, line 1, delete "any one of the preceding claims" and insert --claim 1--

therefor;

Claim 6, line 2, delete "etc";

Claim 7, line 1, delete "any one of the preceding claims" and insert --claim 1--

therefor;

09250340-021699
659120-04E05260

669420-0405260

Claim 8, line 1, delete "any one of the preceding claims" and insert --claim 1-- therefor;

Claim 9, line 1, delete "any one of the preceding claims" and insert --claim 1-- therefor;

Claim 13, line 1, delete "any one of claims 1 to 10" and insert --claim 1-- therefor;

Claim 14, line 1, delete "any one of claims 1 to 10" and insert --claim 1-- therefor;

Claim 15, line 1, delete "any one of claims 1 to 10" and insert --claim 1-- therefor;

Claim 16, line 1, delete "any one of claims 1 to 10" and insert --claim 1-- therefor;

Claim 19, line 1, delete "or 18" after the numeral 17;

Claim 20, line 1, delete "or 18" after the numeral 17;

Claim 21, line 1, delete "any one of claims 17 to 20" and insert --claim 17-- therefor;

Claim 22, line 2, delete "etc";

Claim 23, line 1, delete "any one of claims 17 to 22" and insert --claim 17-- therefor;

Claim 24, line 1, delete "any one of claims 17 to 23" and insert --claim 17-- therefor;

Claim 25, line 1, delete "any one of claims 17 to 24" and insert --claim 17-- therefor;

Claim 29, line 1, delete "any one of claims 17 to 26" and insert --claim 17-- therefor;

Claim 30, line 1, delete "any one of claims 17 to 26" and insert --claim 17-- therefor;

Claim 31, line 1, delete "any one of claims 17 to 26" and insert --claim 17-- therefor;

Claim 32, line 1, delete "any one of claims 17 to 26" and insert --claim 17-- therefor;

Please cancel Claims 33 and 34 without prejudice.

REMARKS

The subject application claims priority under 35 U.S.C. § 119 to Malaysian Patent Application No. PI 9800664 filed February 17, 1998.

Claims 3-9, 13-16, 19-25 and 29-32 have been amended and Claims 33-34 have been canceled without prejudice. The amendments have been made to place the claims in proper condition for examination. No new matter has been added to the subject application.

Early and favorable consideration of the subject application is respectfully requested.

February 16, 1999

Respectfully submitted,



Scott D. Wolsy

Reg. No. 35,413

Attorneys for Applicants

CUMMINGS & LOCKWOOD

Four Stamford Plaza

P.O. Box 120

Stamford, CT 06904

Telephone: (203) 351-4289

S4936491.DOC 02/16/99

IMPROVEMENTS IN CODE BASED ACCESS SYSTEMS

The present invention relates to improvements in code based access systems.

5 Systems in which transactions or connections between two or more parts or stations of the system are conducted or established by means of an access code are known. Such systems include computer terminals wherein the access code is a password, bank terminals such as ATM machines wherein the access code is a personal identification number (PIN) and communications terminals such as
10 mobile telephones wherein the access code is an electronic serial number (ESN). Typically the access code is provided by a user to an accessing part or station of the system and is verified against a duplicate version of the access code available to an accessed part or station of the system, before an authority to perform the transaction or to establish the connection between the stations or
15 parts is given.

A disadvantage of such systems is that the security of future transactions or connections becomes seriously compromised if the access code is detected by or otherwise becomes known to unauthorised persons ie. persons other than the
20 person or persons authorized to perform the transaction or establish the connection.

An object of the present invention is to provide a code based access system which alleviates the disadvantages of the prior art or at least provides the public
25 with a choice.

To this end the present invention provides a system including at least two parts or stations wherein a transaction or connection between any two or more of said parts or stations is conducted or established by means of an access code, said
30 access code being available to an accessed part or station and requiring an identical access code to be provided to an accessing part or station at the time of conducting the transaction or establishing the connection, wherein said access

code is one of a plurality of codes provided to said accessed part or station and available to said accessing part or station, said access code being selected from said plurality of codes at the time of conducting the transaction or establishing the connection such that no two transactions are conducted or no two connections are established with the same access code.

Once an access code has been used to conduct a transaction or establish a connection between the two parts or stations it may be deleted from the system or otherwise disabled. This may avoid the risk that the access code will be reused by the system.

The plurality of access codes may be generated in any suitable manner and by any suitable means. The means for generating the access code preferably is capable of generating non-repeating sequences of characters or numbers. In one form the plurality of codes may be generated via a pseudo random generator. In another form the plurality of codes may be generated via a custom designed software program. The basis for the software program should be randomness and free combination. In one form the software program may be a spreadsheet type program wherein a regular grid or pattern of characters or numbers can be mixed in a controlled manner to produce non-repeating sequences of characters and/or numbers.

The characters/numbers may include arabic numerals, Roman numerals, letters of the alphabet, morse codes etc. in any order or combination. Preferably the access codes are generated independently of or external to the system. Such an approach may enhance security of the overall system by reducing risks associated with systems in which variable codes are generated internally.

The system of the present invention may include first code storage means associated with the accessing part or station of the system, such as an ATM terminal, personal computer, mobile telephone or the like. The first code storage means is adapted for storing one copy of the plurality of codes. The system may

include second code storage means associated with the accessed part or station of the system, such as a bank or other service computer system or telephone exchange. The second code storage means is adapted for storing a second copy of the plurality of codes identical to the one copy stored in the first storage means.

- 5 The first storage means may be incorporated into or with a transaction card such as an ATM card, a computer diskette, a smart card or integrated circuit microchip or the like. The first storage means may include a passive carrier such as a magnetic strip or the like or it may include an active carrier such as the integrated circuit microchip. Because a bank terminal system, computer service provider or
10 telephone exchange typically will have a large number of users, the second storage means may be adapted to store a separate plurality of codes for each user. Each plurality of codes may be stored in the second storage means under a separate address. The address may be identified with a unique identity number assigned to each respective user. The identity number may be that users
15 account number or it may be a different number associated with that user.

- It is highly desirable that the last used code be removed or otherwise disabled from the second code storage means at least, as this will minimize the risk that the same code will be reused in a subsequent transaction. This task may be
20 performed by the bank or other service computer system. The last used code may also be erased or otherwise disabled from the first code storage means. This latter task may be performed in any suitable manner and by any suitable means. In one form this may be carried out by application of heat or mechanical marking not unlike the manner in which a telephone card is disabled according to
25 its level of use.

When a user with an ATM card having a particular identity number, say 9876, approaches an ATM terminal to make a transaction, the following sequence of events may take place:

30

- (i) The bank computer system requests an unused code from the plurality of codes stored by the first code storage means, eg. the ATM transaction

card. The unused code will typically be the next unused code of the plurality of codes, but the plurality of codes may be used in any predetermined sequence;

5 (ii) The bank computer requests the next unused code of the plurality of codes stored by the second code storage means under an address for the ATM card having identity number 9876;

10 (iii) Upon receipt of the respective codes from the first and second code storage means the bank computer compares the codes looking for a perfect match;

15 (iv) A perfect match between the two codes is interpreted as a successful verification of the identity of the users transaction card, and card number 9876 is granted permission to proceed with the transaction;

20 (v) A mismatch between the two codes is interpreted as an unsuccessful verification of the identity of the users transaction card and card number 9876 is denied permission to proceed with the transaction;

25 The present invention also provides a method of conducting a transaction or establishing a connection between at least two parts or stations by means of an access code, said access code being available to an accessed part or station at the time of conducting the transaction or establishing the connection and requiring an identical access code to be provided to an accessing part or station, said method including the steps of:

making available a plurality of codes to said accessed and said accessing parts or stations;

30 selecting, at the time of conducting the transaction or establishing the connection, one code from said plurality of codes; and

using said selected code to conduct the transaction or establish the connection such that no two transactions are conducted or no two connections are established with the same access code.

- 5 The access code system of the present invention may be used in place of an existing or conventional access code system or systems or it may be used in addition to an existing or conventional access code system or systems to upgrade the security of the latter. The improved system provided by the present invention may be incorporated into a newly designed code based access system or it may
10 be provided by modifying an existing system. To distinguish access codes according to the present invention from prior art codes they will hereinafter be referred to as "secondary" codes.

- The system of the present invention may be used to enhance security of a door
15 opening apparatus, in particular door opening apparatus which makes use of an electronic key for accessing secure areas such as safes, strong rooms, high security areas or the like. In the latter embodiment a set of secondary security codes according to the present invention may be loaded to a first code storage means associated with the accessed part of the system. The accessed part may
20 be a user inaccessible part of the door opening apparatus. The first code storage means may include an integrated circuit microchip, magnetic strip, smart card, computer diskette or the like. An identical set of codes may be made available to the accessing part of the system. The accessing part may be a user accessible part of the door opening apparatus. The accessing part may include an electronic
25 key. The electronic key may include a second code storage means for storing an identical set of security codes. The second code storage means may include a magnetic strip, smart card, integrated circuit microchip computer diskette or the like.

- 30 Preferred embodiments of the present invention will now be described with reference to the accompanying drawings wherein:-

Fig. 1 shows a diagrammatic representation of one form of application of the present invention to bank terminals;

Figs. 2A, 2B and 2C show front, rear and cross-sectional views respectively of a
5 dummy ATM card;

Figs. 3A, 3B and 3C show empty, loaded and cross-sectional views respectively of a carrier strip transfer apparatus;

10 Fig. 4 shows a cross-sectional view of an ATM card with carrier strip installed;

Fig. 5 shows a diagrammatic representation of one form of application of the present invention to a mainframe computer system;

15 Fig. 6 shows a diagrammatic representation of one form of application of the present invention to a mobile transceiver; and

Fig. 7 shows a diagrammatic representation of one form of application of the present invention to a door opening apparatus.

20

Referring to Fig. 1, there is shown an ATM access card 10 which serves as a carrier for secondary codes according to the present invention. In addition to the known magnetic strip (not shown) which carries the account number of the client, ATM card 10 includes a carrier strip 11 in which are stored secondary codes
25 according to the present invention. Prior to using ATM card 10 at an ATM terminal 12, ATM card 10 is inserted into a dedicated disc drive of a Personal Computer (PC) 13. PC 13 is programmed to generate a non-repeating set of 100 secondary codes 14 and to write the set of codes 14 into carrier strip 11. An identical set of 100 codes is sent to data storage module 15 associated with the
30 bank's main computer system 16. The set of codes 14 may optionally be sent to code replacement module 17 where they may be held temporarily pending transfer to storage module 15. After the set of codes have been written into

carrier strip 11 and storage module 15 or code replacement module 17, PC 13 is programmed to delete the code set from its memory. This enhances security of the system by ensuring that no additional copies of the code set remain in existence.

5

ATM card 10 which carries identification serial number 9876 may then be inserted into a (modified) card slot associated with ATM terminal 12. The holder of ATM card 10 may key in his PIN number to commence a transaction and this may continue to provide a primary level of security as is known in the art. To provide a secondary level of security according to the present invention, main computer 16 sends a request A to ATM terminal 12 for the first unused code (ABCDEF) from the set 14 of 100 codes written into carrier strip 11 associated with ATM card 10. Main computer 16 also sends a request B for the first unused code from the identical set of 100 codes stored in data storage module 15 under an address for the ATM card carrying identification serial number 9876.

ATM terminal 12 sends reply C to computer 16 including the first unused code (ABCDEF) from carrier strip 11 and data storage module 15 sends reply D including the first unused code stored under the address corresponding to ATM card bearing serial number 9876. When computer 16 identifies a match between the codes included in replies C and D, it interprets this as a successful verification of the identify of ATM card 10 bearing serial number 9876 and grants permission E to ATM terminal 12 to proceed with the transaction.

When computer 16 identifies a mismatch between the codes included in replies C and D, it interprets this as an unsuccessful verification of the identity of ATM card 10 bearing serial number 9876 and denies permission to ATM terminal 12 to proceed with the transaction. A mismatch between the codes included in replies C and D indicates that an unauthorized penetration of the banking system may have taken place. Instead of barring further transactions in the event of a mismatch between the codes included in replies C and D, computer 16 may be programmed to request another code set each from ATM terminal 12 and data

storage module 15. Preferably computer 16 is programmed to request three further code sets each from ATM terminal 12 and data storage module 15. If three consecutive code sets do not match, computer 16 may reasonably assume that the banking system has been penetrated by unauthorized elements and may
5 bar further transactions of the account via the ATM card. Even if two out of three codes match computer 16 may still bar the transaction. Computer 16 may continue to request codes for verification until it has three consecutive matches, and may then return ATM card 10 to the user but not issue cash.

10 Computer 16 may advise the user via the screen associated with ATM terminal 12 to contact the local branch of his bank and seek assistance eg. to have his account number and/or code sets changed. The detected instance of potential breach of ATM card security may be recorded and communicated to the user immediately via telephone/fax/mail and/or the next authorized transaction made
15 by the user.

When the holder of the ATM card commences a subsequent transaction, computer 16 sends a request to ATM terminal 12 for the second unused code (1234567). This process continues until all 100 secondary codes have been used
20 up one at a time. When all 100 codes sets have been used up the user will be advised via ATM terminal 12 to contact his bank to have the defunct carrier strip 11 replenished with a fresh set of 100 codes. Carrier strip 11 may be replenished by rewriting. Alternatively, if the technique used for disabling/deleting used codes has harmed the integrity of carrier strip 11, carrier strip 11 may be removed from
25 the ATM card and replaced with a fresh carrier strip. The fresh carrier strip may be supplied to be bank branch from a central location already written with a new set of 100 codes. The fresh carrier strip may be supplied attached to a blank or dummy card to facilitate handling, programming and transfer of the carrier strip to a customer's ATM card.

30 Referring to Figs. 2A-C there is shown a dummy card 20 formed from 0.4mm thick plastics. This is about half the thickness of an ATM card. Fresh carrier strip

firmly against lower panel 27 of the apparatus. This causes embossing bar 29 to lift to a position about level with the non-recessed face of panel 27, breaking perforated edges 23 and causing carrier strip 21 to lodge into recess 10A in ATM card 10 (refer Fig. 4). Upon opening of the apparatus, transfer of carrier strip 21 from dummy card 20 to the customers ATM card 10 should be complete.

Transfer of carrier strip 21 from dummy card 20 to the customers ATM card 10 may also be performed manually. This may be done by firstly removing the cover 25 from adhesive layer 24 and placing dummy card 20 on top of ATM card 10, both in an upright and face up position. The two cards may be held firmly together eg. by means of adhesive tape applied to the tops and sides of the cards. The two cards should then be placed on a hard surface such as the edge of a table and an embossing bar approximately equal in dimensions to carrier strip 21 (78 mm x 4mm) placed on the top of carrier strip 21. The embossing bar should then be pressed down firmly with both thumbs. The thumbs may be slid along the length of the embossing bar until carrier strip 21 breaks away from dummy card 20 along its perforated edges 23 and is pushed into recess 10A in ATM card 10. The adhesive tapes may then be removed and transfer of carrier strip 21 to ATM card 10 should be complete.

Each bank branch may hold a large number of dummy cards with attached replacement carrier strips. To maintain security of the allocation process the customer may select at random a replacement carrier strip from a batch of say 1000 replacement strips. When the customer selects his carrier strip it is affixed to his ATM card and the central bank computer is notified of the choice. The central bank computer then associates its second copy of the set of codes identical to the chosen replacement strip with the customers account or other identification number.

The system shown in Fig. 5 protects a mainframe computer system 40 from hacking by way of external links to the computer system 40. Security is typically provided in this context by way of a common password for all authorized users of

computer system 40 and optionally another password for individual users. The passwords are usually changed once a week. This allows a hacker who gains access to the password or passwords to commit repeated break-ins over the period of currency of the password(s) and to gain access to confidential
5 information and corrupt the system with unauthorized data or a virus.

The present invention allows operators of computer systems to substantially limit risk of random break-ins and to avoid repeated break-in activities.

10 Referring to Fig. 5 there is shown a personal computer (PC) 41 connected to computer system 40 via connection 42 such as the internet, and a verification module 43. Before access to computer system 40 can be granted verification module 43 must receive a valid code(s) from PC 41. The valid code(s) may include the usual password or passwords and includes a secondary code
15 according to the present invention. A set of secondary codes 44a may be stored on an authorization diskette 44 which serves as a carrier for the secondary codes. Diskette 44 is adapted to store 100 sets of secondary codes. The set of secondary codes 44a is loaded to diskette 44 via PC 45 belonging to or being under the control of the owner or operator of computer system 40.

20 Once it is loaded with the secondary codes 44a diskette 44 is supplied via a secure route to the authorized user of computer system 40. The authorized user is obliged to store diskette 44 in a secure and preferably locked or otherwise restricted location. Diskette 44 will typically be available for use with a designated
25 PC/terminal ie. a terminal having a specific E-mail address, unless a roaming authority has been granted.

Diskette 44 should only need to be sent to new clients or first time users (including replacements for lost, barred and malfunctioning disks) because
30 subsequent replacements codes (ie. after a current set of 100 codes has been used up) can be sent to the user's PC 41 via connection 42 after it has been verified. A set of 100 secondary codes identical to the set loaded to diskette 44 is

sent from PC45 to storage module 46 associated with verification module 43. The set of codes may optionally be sent to code replacement module 47 where they may be held temporarily pending transfer to storage module 46.

- 5 When a user requests access to computer system 40 and (optionally) keys in his passwords into PC41, verification module 43 sends a request to PC41 via connection 42 for the first unused code from the list of 100 codes stored on diskette 44. Module 43 also sends a request A for the first unused code from the identical set of 100 codes stored in storage module 46 under an address specific
10 to PC41. PC41 sends a reply to verification module 43 including the first unused code stored on diskette 44, and storage module 46 sends reply B to verification module 43 including the first unused code stored under the address which corresponds to PC41. When verification module 43 identifies a match between the codes received from PC 41 and storage module 46 it interprets this as a
15 successful verification of the identity of PC41 and grants access to PC41 to connect to computer system 40.

- Even if the first set of codes is not immediately deleted after use for any reason, the verification software should be programmed so that it avoids reusing a
20 previously used code. When the user next requests access to computer system 40, verification module 43 sends a request for the second unused code. This process continues until all 100 secondary codes have been used up one at a time. Diskette 44 will then be defunct as it has no more verification codes available and must be replenished or replaced.

- 25 In one form a code replacement program may be activated upon positive verification of an access using the last or 100th code. Upon detecting a verification which utilizes the 100th code, code replacement module 47 is activated to choose at random a new group of 100 secondary codes stored in
30 module 47 and to download this to diskette 44 via line 48, module 43, line 42, and PC41. During this process an image appears on the screen of PC41 warning the user not to remove diskette 44 from PC41. Module 47 also loads an identical set

of codes to storage module 46. The verification software may then assign via line 49 the identity of PC41, such as its E-mail address, to the set of codes just loaded to storage module 46. Code replacement module 47 may hold a large stock of unused code sets (eg. 1000) ready to be downloaded upon receiving a request
5 from verification module 43.

When verification module 43 identifies a mismatch between the codes received from PC41 and module 46 it interprets this as an unsuccessful verification of the identity of PC41 and denies further access to PC41 to connect to computer
10 system 40. A mismatch between the codes received from PC41 and module 46 indicates that an unauthorized penetration of the computer system may have taken place. The user is advised of this status and of the need for increased security/access to PC41 to prevent further unauthorized activities and/or the need to change passwords, diskette 44 etc.

15 Instead of barring further access in the event of a mismatch between the codes, module 43 may be programmed to request another code set each from PC41 and data storage module 46. Preferably module 43 is programmed to request a further three code sets each from PC41 and data storage module 46. If three
20 consecutive code sets do not match, module 43 may reasonably assume that the computer system has been penetrated by unauthorized elements and may bar further access to PC41. Even if two out of three codes match module 43 may still bar access. Module 43 may continue to request codes for verification until it has three consecutive matches, and only then may grant access to PC41.

25 The system shown in Fig. 6 protects a mobile transceiver such as a cellular telephone from unauthorized use. Security is typically provided in this context by means of an electronic serial number (ESN) which establishes the identity and authenticity of an incoming call placed through a host transceiver. During the
30 process of registration and activation of a new cellular telephone, matching sets of ESNs are respectively placed in the mobile transceiver and in the data bank of a main telephone exchange.

When a call is placed through the mobile transceiver, the transceiver transmits its ESN followed by the telephone number of a recipient transceiver. The transmitted signal is relayed via a receiving dish to the data bank of the telephone exchange. The ESN of the mobile transceiver is then compared to the matching ESN in the databank. When a match is established, the call is recognized by the telephone exchange as genuine and is authorized passage to the next stage (where no match is established between the transceiver ESN and the data bank ESN, the call is rejected and refused passage through the main exchange). The telephone number of the recipient transceiver is then sent by the telephone exchange to a transmitting tower for transmission to the recipient transceiver.

Referring to Fig. 6, there is shown a host transceiver 50 linked to a recipient transceiver 51 (not shown) via telephone exchange 52 and respective transceiver stations 53, 54. Before access to recipient transceiver 51 can be granted, telephone exchange 52 must receive a valid code(s) from host transceiver 50. The valid code(s) may include a conventional ESN and includes a secondary code according to the present invention. A set of secondary codes may be stored in an integrated circuit microchip/smart card (IC) 55 fitted to host transceiver 50.

IC 55 is in addition to the usual ESN integrated circuit microchip/smart card 56 fitted to host transceiver 50. IC 55 is adapted to store 500 sets of secondary codes 55a. The set of secondary codes 55a is transferred to IC 55 via PC 57 belonging to or being under control of the owner or operator of telephone exchange 52. PC 57 includes a dedicated IC writer for this purpose. Once IC 55 is programmed, it is sent to a local branch office of the telephone service operator or his agent for installation to a new subscriber's transceiver or for replacement of a defunct IC ie. an IC which has exhausted all of its secondary codes.

A set of 500 secondary codes identical to the set 55a stored in IC 55 is sent from PC 57 to storage module 58 associated with telephone exchange 52. The set of

codes may optionally be sent to code replacement module 59 where they may be held temporarily pending transfer to storage module 58.

When host transceiver 50 places an outgoing call it transmits its ESN which is
5 picked up by transceiver station 53 and relayed to telephone exchange 52. The transmitted ESN is then compared to the matching ESN in the data bank of telephone exchange 52. When a match is established the ESN is recognized by telephone exchange 52 as legitimate and the call is authorized passage to the next stage.

10

According to the present invention telephone exchange 52 sends a request A to host transceiver 50 via transceiver station 53 for the first unused code from the set of 500 codes 55a stored in IC 55. Telephone exchange 52 also sends a
15 request B for the first unused code from the identical set of 500 codes stored in storage module 58 under an address specific to host transceiver 50. In practice the storage address may be associated with the unique ESN assigned to host transceiver 50.

Host transceiver 50 sends a reply C including the first unused code stored in IC
20 55 to telephone exchange 52 and storage module 58 sends reply D to telephone exchange 52 including the first unused code stored under the address which corresponds to host transceiver 50. When telephone exchange 52, identifies a match between the codes included in replies C and D, it interprets this as a successful verification of the identity of host transceiver 50 and allows the
25 telephone number of the recipient transceiver 51 sent by host transceiver 50, to be transmitted to transceiver station 54 and relayed to recipient transceiver 51.

Even if the first set of codes is not immediately deleted after use for any reason, the verification software should be programmed so that it avoids reusing a
30 previously used code. When the subscriber next places an outgoing call, telephone exchange 52 sends a request for the second unused code. This process continues until all 500 secondary codes have been used up one at a

time. IC55 will then be defunct as it has no more verification codes available and must be replenished/replaced.

When all 500 codes have been used up (in practice this may be a lesser number
5 to allow some reserve calls to be made before receiving a replacement for IC 55)
the telephone exchange can advise the subscriber (eg. by means of a recorded
message following verification of, say, the 490th call) to contact his local branch
to have the defunct (or soon to be defunct) IC 55 replaced with a fresh IC. The
fresh IC may be supplied to the branch office already loaded with a new set of
10 500 codes. Each branch office may hold a large number of replacement IC's. To
maintain security of the allocation process the subscriber may select at random a
replacement IC from a batch of, say, a 1000 replacement ICs. When the
subscriber selects his/her IC it may be fitted to his transceiver and the telephone
exchange notified of the choice. The telephone exchange may then associate its
15 second copy of the set of codes identical to the chosen replacement IC with the
subscribers ESN or other identification number.

IC 55 may be located in an easily accessible position in the associated
transceiver to enable replacement of defunct ICs. In some embodiments IC 55
20 may comprise a smart card. IC 55 also may be integrated with ESN IC 56.
Typically a transceiver will require modification to accommodate IC55. This may
be done by way of a sliding carrier not unlike a smart card. New transceivers may
be constructed with a built-in slot for receiving IC 55 and/or associated carrier.

25 Referring to Fig. 7, there is shown a safe/strong room 60. Safe/strong room 60
includes a code based door opening apparatus according to the present
invention.

The door opening apparatus includes a first code storage means associated with
30 a user inaccessible part of the door opening apparatus. The first code storage
means is adapted for storing a set of secondary codes 61. The first code storage
means include a computer diskette 62. The diskette 62 may be adapted to store

100 sets of secondary codes. The set of secondary codes 62 is loaded to diskette 62 via PC 63.

Once it is loaded with secondary codes 61 diskette 62 is installed to the user
5 inaccessible part of the door opening apparatus.

PC 63 is used to load an identical set of secondary codes 61 to a second diskette 64. Diskette 64 is in possession of the owner of safe/strong room 60 or other authorized person, who is obliged to store diskette 64 in a secure and preferably
10 locked or otherwise restricted location. When the owner/authorized person requires access to safe/strong room 60, diskette 64 serves as an electronic key to activate the door opening apparatus and gain access to safe/strong room 60.

When diskette 64 is inserted into the user accessible part of the door opening
15 apparatus associated with safe/strong room 60, the door opening apparatus requests the first unused code from the list of 100 codes stored on diskette 62. The door opening apparatus also requests the first unused code from the identical set of 100 codes stored in diskette 64. When the door opening apparatus identifies a match between the codes received from diskette 62 and
20 diskette 64 it interprets this as a successful verification of the identity of the electronic key and opens the door.

Finally, it is to be understood that various alterations, modifications and/or additions may be introduced into the constructions and arrangements of parts
25 previously described without departing from the spirit or ambit of the invention.

CLAIMS

1. A system including at least two parts or stations wherein a transaction or connection between any two or more of said parts or stations is conducted or established by means of an access code, said access code being available to an accessed part or station and requiring an identical access code to be provided to an accessing part or station at the time of conducting the transaction or establishing the connection, wherein said access code is one of a plurality of codes provided to said accessed part or station and available to said accessing part or station, said access code being selected from said plurality of codes at the time of conducting the transaction or establishing the connection such that no two transactions are conducted or no two connections are established with the same access code.
2. A system according to claim 1 wherein said selected code is removed from said system or is otherwise disabled after it has been used to conduct a transaction or establish a connection between said accessed and accessing parts or stations.
3. A system according to claim 1 or 2 wherein said plurality of codes is generated by means of a pseudo random generator.
4. A system according to claim 1 or 2 wherein said plurality of codes is generated by means of a software program arranged to produce non-repeating sequence of codes.
5. A system according to any one of the preceding claims wherein each code includes a sequence of characters and/or numbers.
6. A system according to claim 5 wherein said characters and/or numbers include Roman numerals, letters of the alphabet, morse codes etc.

7. A system according to any one of the preceding claims wherein the plurality of codes is generated external to said system.
8. A system according to any one of the preceding claims wherein said plurality of codes is at least 100.
9. A system according to any one of the preceding claims including first code storage means associated with said accessing part or station for storing one copy of said plurality of codes.
10. A system according to claim 9 including second code storage means associated with said accessed part or station for storing a second copy of said plurality of codes identical to said one copy stored in said first storage means.
11. A system according to claim 9 wherein said first code storage means includes one of an ATM transaction card, a smart card, an integrated circuit microchip and a computer diskette.
12. A system according to claim 10 wherein said second code storage means is associated with one of a bank computer system, a service provider computer system and a telephone exchange.
13. A system according to any one of claims 1 to 10 wherein at least one said part or station includes an ATM terminal.
14. A system according to any one of claims 1 to 10 wherein at least one said part or station includes a PC or computer terminal.
15. A system according to any one of claims 1 to 10 wherein at least one said part or station includes a mobile transceiver.

16. A system according to any one of claims 1 to 10 wherein at least one said part or station is associated with a door opening apparatus.
17. A method of conducting a transaction or establishing a connection
5 between at least two parts or stations by means of an access code, said access code being available to an accessed part or station at the time of conducting the transaction or establishing the connection and requiring an identical access code to be provided to an accessing part or station, said method including the steps of:
making available a plurality of codes to said accessed and said accessing
10 parts or stations;
selecting, at the time of conducting the transaction or establishing the connection, one code from said plurality of codes; and
using said selected code to conduct the transaction or establish the connection such that no two transactions are conducted or no two connections
15 are established with the same access code.
18. A method according to claim 17 wherein said selected code is removed from said accessed part or station or is otherwise disabled after it has been used to conduct a transaction or establish a connection between said accessed and
20 accessing parts or stations.
19. A method according to claim 17 or 18 wherein said plurality of codes is generated by means of a pseudo random generator.
20. A method according to claim 17 or 18 wherein said plurality of codes is
25 generated by means of a software program arranged to produce non-repeating sequence of codes.
21. A method according to any one of claims 17 to 20 wherein each code
30 includes a sequence of characters and/or numbers.

22. A method according to claim 21 wherein said characters and/or numbers include Roman numerals, letters of the alphabet, morse codes etc.
23. A method according to any one of claims 17 to 22 wherein the plurality of
5 codes is generated external to said at least two parts or stations.
24. A method according to any one of claims 17 to 23 wherein said plurality of codes is at least 100.
- 10 25. A method according to any one of claims 17 to 24 including providing first code storage means associated with said accessing part or station for storing one copy of said plurality of codes.
- 15 26. A method according to claim 25 including providing second code storage means associated with said accessed part or station for storing a second copy of said plurality of codes identical to said one copy stored in said first storage means.
- 20 27. A method according to claim 25 wherein said first code storage means includes one of an ATM transaction card, a smart card, an integrated circuit microchip and a computer diskette.
- 25 28. A method according to claim 26 wherein said second code storage means is associated with one of a bank computer system, a service provider computer system and a telephone exchange.
29. A method according to any one of claims 17 to 26 wherein at least one said part or station includes an ATM terminal.
- 30 30. A method according to any one of claims 17 to 26 wherein at least one said part or station includes a PC or computer terminal.

31. A method according to any one of claims 17 to 26 wherein at least one said part or station includes a mobile transceiver.

32. A method according to any one of claims 17 to 26 wherein at least one
5, said part or station is associated with a door opening apparatus.

33. A system according to claim 1 substantially as herein described with reference to Fig. 1 or Figs. 2A, 2B, 3A, 3B, 3C and 4 or Fig. 5 or Fig. 6 of the accompanying drawings.

10

34. A method according to claim 17 substantially as herein described with reference to Fig. 1 or Figs. 2A, 2B, 3A, 3B, 3C and 4 or Fig. 5 or Fig. 6 of the accompanying drawings.

095040 01605260

ABSTRACT

A system including at least two parts or stations wherein a transaction or connection between any two or more of the parts or stations is conducted or established by means of an access code, the access code being available to an accessed part or station and requiring an identical access code to be provided to an accessing part or station at the time of conducting the transaction or establishing the connection. The system is characterized in that the access code is one of a plurality of codes provided to the accessed part or station and available to the accessing part or station. The system is further characterized in that the access code is selected from the plurality of codes at the time of conducting the transaction or establishing the connection, such that no two transactions are conducted or no two connections are established with the same access code.

15

CODE SET NUMBER	
1	ABCDEF
2	1234567
3	•••••
4	-2BT4•7
5	R2D2xZ
6	C3PO•-K
7	UCELOXX
8	7890DD
9	•-ABC123
100 SETS	




FIG1




FIG 2A




FIG 2B




FIG 4




FIG 2C




FIG 3B




FIG 3A




FIG 3C




FIG 5





FIG 6



Declaration, Power of Attorney, and Petition

As a below named inventor, I/we hereby declare that:

My/Our residence, post office address and citizenship is/are as stated below next to my/our name(s),

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: IMPROVEMENTS IN CODE BASED ACCESS SYSTEMS, the specification of which (*check one*)

☒ is attached hereto; or

☐ was filed on _____ as Application Serial No. _____ and was amended on _____ (if applicable); or

PCT FILED APPLICATION ENTERING NATIONAL STAGE

☐ was described and claimed in International Application No. _____ filed on _____ and as amended on _____ (if applicable).

I/We hereby state that I/we have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above, and that it contains a full, clear, concise and exact description of the subject matter for which a patent is sought.

I/we acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

Prior Application(s)

☒ (Check if applicable) I/We hereby claim foreign priority benefits under Title 35, United States Code § 119, by checking the box(es) below, any foreign application(s) for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

			Priority	
Claimed				
PI9800664	Malaysia	17 February 1998	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	Day/month/year filed	Yes	No
_____	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	Day/month/year filed	Yes	No

☐ (Check if applicable) I/We hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

Prior Provisional Application(s)

_____	_____
(Application Number)	(Filing Date)
_____	_____
(Application Number)	(Filing Date)

669720 04E05260

(Note: When the nonprovisional application is entitled to an earlier U.S. effective filing date of one or more provisional applications under Title 35, United States Code § 119(e), a statement such as "This application claims the benefit of U.S. Provisional Application No. _____, filed _____, and U.S. Provisional Application No. _____, filed _____." should appear as the first sentence of the description. In view of this requirement, the right to rely on a prior application may be waived or refused by an applicant by refraining from inserting a reference to the prior application in the specification of the later one.)

☐ (Check if applicable) I/We hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I/we acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Prior U.S. Application(s)

(Application Serial No.)	(Filing Date)	Status (Patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	Status (Patented, pending, abandoned)

☐ (Check if applicable) I/We hereby authorize the U.S. attorneys or agents named herein to accept and follow instructions from _____ as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorneys or agents named herein and myself/ourselves. In the event of a change, I/we will notify in writing the U.S. attorney or agent named herein.

☐ (Check if applicable) In this continuation-in-part application, insofar as the subject matter of any of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

I/We hereby declare that all statements made herein of my/our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I/we hereby appoint the attorneys whose names are associated with United States Patent and Trademark Office Customer Number 21832:



021832

PATENT TRADEMARK OFFICE
Bar Code Above

Barry Kramer, Reg. No. 20,622
Neil G. Cohen, Reg. No. 35,100
Mark Giarrantana, Reg. No. 32,615
Joseph Kentoffio, Reg. No. 33,189
James W. Jakobsen, Reg. No. 38,505
Victoria M. Malia, Reg. No. 39,359

Jeffrey J. Miller, Reg. No. 39,773
Steven J. Moore, Reg. No. 35,959
Basem E. Nabulsi, Reg. No. 31,645
R. Thomas Payne, Reg. No. 30,674
Scott D. Wofsy, Reg. No. 35,413

of the firm of CUMMINGS & LOCKWOOD, whose address is Four Stamford Plaza, P.O. Box 120, Stamford, Connecticut 06904-0120, as my/our attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Please address all written correspondence to the address associated with United States Patent and Trademark Customer Number 21832:

CUMMINGS & LOCKWOOD
Granite Square
700 State Street
P.O. Box 196020
New Haven, CT 06509-1960
Fax (203) 351-4535

Telephone Calls should be directed to Scott D. Wofsy, by dialing (203) 351-4289.

Wherefore I/we pray that Letters Patent be granted to me/us for the invention or discovery described and claimed in the foregoing specification and claims, and I/we hereby subscribe my name to the foregoing specification and claims, declaration, power of attorney, and this petition.

Full name of first inventor:

Sia Yik HEI

Residence:

Lot PT 4406

Kawasan Perindustrian Teluk Kalong

24000 Kemaman, Terengganu Darul Ehsan, Malaysia

Citizenship:

Malaysia

Post Office Address:

Lot PT 4406

Kawasan Perindustrian Teluk Kalong

24000 Kemaman, Terengganu Darul Ehsan, Malaysia

Inventor's signature

Date:

Full name of second inventor:

Residence:

Citizenship:

Post Office Address:

Inventor's signature

Date:

S4938921.DOC 02/16/99